

Main Performances

- **Execution** Without housing. It is necessary that housing has to be realized by end user according to the armonized rules to ensure an appropriate protection
- **Positioning** Vertical axis
- **Inside passage** 42mm diameter trough steel pipe for the passage of cable, hoist rope, hydraulic pipes or piston shaft.
- **Connections** Directly on the terminal box for the rings and on the brush-holders clamps.
- **Brushes** 50 A blade or copper-graphite
- **Executions** From 4 to 14 rings 50 A
- **Armonized rules** 2014/35/UE - 2014/30/UE - 2006/42/CE – RoHS 2011/65/UE Directives
- **Marking** CE



Electrical Features

- **Rated Voltage** 660 V ac - dc
- **Rated Current** Ith 50 A
- **Degree protection** IP 00
- **Maximum speed** 30 rpm
- **Test Voltage** 2,5 kV
- **Operating Temperature** - 20 °C + 60 °C



Standard Executions

50 A					
Articoli	No. Anelli	H - mm	F - mm	G - mm	P - mm
G G90D4L	4	210	189	49	80
G G90D6L	6	250	235	49	120
G G90D8L	8	280	281	39	160
G G90D10L	10	330	304	49	200
G G90D12L	12	370	350	49	240
G G90D14L	14	400	396	39	280

For cooper-graphite executions the code is without the final letter L.

Dimensions

