


Main Features

- **Execution** Without housing. It is necessary that housing has to be realized by end user according to the armonized rules to assure a suitable protection
- **Positioning** Vertical axis
- **Inside passage** Diameter 47mm suitable for cables passages, ropes and so on
- **Cable connections** Directly on the terminal box for the rings and on the brush-holders terminals
- **Brushes** 20 A and 60 A in copper-graphite. Signals between rings and brushes secured by a "V" special contact.
- **Executions** From 4 to 36 rings 20 A - mixed executions 20 A / 60 A
- **Armonized rules** 2014/35/UE - 2014/30/UE - 2006/42/CE - RoHS 2011/65/UE
- **Marking** CE



Electrical Features

- **Rated Voltage** 660 V ac - dc
- **Rated Current** Ith 20 A - 60 A
- **Degree protection** IP 00
- **Maximum speed** 30 rpm
- **Test Voltage** 2,5 kV
- **Operating Temperature** - 20 °C + 60 °C

Standard Executions

20 A			
Articoli	No. Anelli	H - mm	F - mm
G PS1B18	18	255	300
G PS1B24	24	300	345
G PS1B30	30	345	390
G PS1B36	36	390	435

Availability on demand:

- Mixed executions with 20 A / 60 A rings

Dimensions

